

**1. TBS AquaLOCK® System Door****1.1 Type NTG3-V2****1.1.1 Flood Protection Door "AquaLOCK," not thermally separated, up to 3m water level, Locking version V2**

**NTG3 Flood Protection Door.** Tested according to DIN EN 12046-2:2000-02

Evaluation according to EN 14351-1:2006, ISO 12567-1:2010,

Brand: AquaLOCK

Single-wing door element. Stop type DIN right or DIN left.

Door leaf and frame galvanized and painted according to RAL, 53mm thick, welded steel cover plate 3mm, double trapezoidal seal made of high-pressure-resistant silicone on four sides. Rectangular frame, 2.0 mm thick. Mortise lock with profile cylinder lockable from both outside and inside, with 3 keys. Inside and outside with silver aluminium handle set on round rose. Patented hinge system for optimal sealing function, optionally with ball bearing. Central friction bolt lock for easy activation of flood resistance from the inside. Certified flood resistance according to IFT guideline FE-07/1-2005 for a water level of up to 3m.

Installation dimension (W x H mm) : \_\_\_\_\_ x \_\_\_\_\_

Quantity: \_\_\_\_\_

Supply and install according to manufacturer's instructions.

**Size range:**

Width: 600 - 1200 mm

Height: 800 - 2300 mm

**Stop type:**

☐ DIN right, outward opening

☐ DIN left, outward opening

**Design:**

☐ With glass cut-out

☐ With flood-resistant cylinder cover

**Locks:**

☐ Profile cylinder

☐ Panic locks

☐ Panic bar handle "Pushbar"

☐ Overhead door closer DIN EN 1154

**Manufacturer's proof:**

Torbau Schwaben GmbH

Enzianstraße 14

D-88436 Oberessendorf

Tel.: +49 (0) 7355 -93 100

URL: [www.AquaLOCK.info](http://www.AquaLOCK.info)

Email: [info@AquaLOCK.info](mailto:info@AquaLOCK.info)

Quantity: .....pc

Price: .....€

Total: .....€