

1. TBS AquaLOCK® System Door**1.1 Type NTG3-V6****1.1.1 Flood Protection Door "AquaLOCK," not thermally separated, up to 3m water level, Locking version V6**

NTG3 Flood Protection Door. Tested according to DIN EN 12046-2:2000-02

Evaluation according to EN 14351-1:2006, ISO 12567-1:2010, Burglary protection

DIN EN 1628:2011, DIN EN 1629:2011, DIN EN 1630:2011

Brand: AquaLOCK

Single-wing door element. Stop type DIN right or DIN left.

Door leaf and frame galvanized and painted according to RAL, 53mm thick, welded steel cover plate 3mm, double trapezoidal seal made of high-pressure-resistant silicone on four sides. Rectangular frame 2.0 mm thick, mortise lock with profile cylinder lockable from both outside and inside, with 3 keys. Inside and outside with silver aluminium handle set on round rose. Patented hinge system for optimal sealing function, optionally with ball bearing. Central friction bolt lock for easy activation of flood resistance from both inside and outside. Certified flood resistance according to IFT guideline FE-07/1-2005 for a water level of up to 3m.

Installation dimension (W x H mm) : _____ x _____

Quantity: _____

Supply and install according to manufacturer's instructions.

Size range:

Width: 600 - 1200 mm

Height: 800 - 2300 mm

Stop type:

☐ DIN right, outward opening

☐ DIN left, outward opening

Design:

☐ With glass cut-out

☐ With flood-resistant cylinder cover

☐ With flood-resistant cover for central friction bolt

Locks:

☐ Profile cylinder

☐ Panic locks

☐ Panic bar handle "Pushbar"

☐ Overhead door closer

Manufacturer's proof:

Torbau Schwaben GmbH

Enzianstraße 14

D-88436 Oberessendorf

Tel.: +49 (0) 7355 -93 100

URL: www.AquaLOCK.info

Email: info@AquaLOCK.info

Quantity:pc

Price:€

Total:€