

1. TBS AquaLOCK® System Door**1.1 Type NTG5-V1****1.1.1 Flood Protection Door "AquaLOCK," not thermally separated, up to 5m water level, Locking version V1**

NTG5 Flood Protection Door. Tested according to DIN EN 12046-2:2000-02

Evaluation according to EN 14351-1:2006, ISO 12567-1:2010, EVH Test Number: EVH054/TBS

Brand: AquaLOCK

Single-wing door element. Stop type DIN right or DIN left.

Door leaf and frame galvanized and painted according to RAL, 73mm thick, welded steel cover plate 4mm, double trapezoidal seal made of high-pressure-resistant silicone on four sides. Rectangular frame 4.0 mm thick. Mortise lock with profile cylinder lockable only from the inside, with 3 keys. Inside with silver aluminium handle set on round rose, outside without handle, without locking cylinder. Patented hinge system for optimal sealing function, optionally with ball bearing. Friction bolt locks for easy activation of flood resistance. Flood resistance according to IFT guideline FE-07/1-2005 for a water level up to 5m.

Installation dimension (W x H mm) : _____ x _____

Quantity: _____

Supply and install according to manufacturer's instructions.

Size range:

Width: 600 - 1300 mm

Height: 800 - 2300 mm

Stop type:

☐ DIN right, outward opening

☐ DIN left, outward opening

Locks:

☐ Panic locks

☐ Panic bar handle "Pushbar"

☐ Overhead door closer

Manufacturer's proof:

Torbau Schwaben GmbH

Enzianstraße 14

D-88436 Oberessendorf

Tel.: +49 (0) 7355 -93 100

URL: www.AquaLOCK.info

Email: info@AquaLOCK.info

Quantity:pc Price:€ Total:€