

**1. TBS AquaLOCK® System Door****1. Type NTG5-V6****1.1.1 Flood Protection Door "AquaLOCK," not thermally separated, up to 5m water level, Locking version V6**

**NTG5 Flood Protection Door.** Tested according to DIN EN 12046-2:2000-02

Evaluation according to EN 14351-1:2006, ISO 12567-1:2010, Burglary protection

DIN EN 1628:2011, DIN EN 1629:2011, DIN EN 1630:2011, EVH Test Number: EVH054/TBS

Brand: AquaLOCK

Single-wing door element. Stop type DIN right or DIN left.

Door leaf and frame galvanized and painted according to RAL, 73mm thick, welded steel cover plate 4mm, double trapezoidal seal made of high-pressure-resistant silicone on four sides. Rectangular frame 4.0 mm thick. Mortise lock with profile cylinder lockable from the outside and inside, with 3 keys. Inside and outside with silver aluminum handle set on round rose. Patented hinge system for optimal sealing function, optionally with ball bearing. Two friction bolt locks for easy activation of flood resistance from both the inside and outside. Flood resistance according to IFT guideline FE-07/1-2005 for a water level up to 5m.

Installation dimension (W x H mm) : \_\_\_\_\_ x \_\_\_\_\_

Quantity: \_\_\_\_\_

Supply and install according to manufacturer's instructions.

**Size range:**

Width: 600 - 1300 mm

Height: 800 - 2300 mm

**Stop type:**

☐ DIN right, outward opening

☐ DIN left, outward opening

**Design:**

☐ with flood-resistant cylinder cover

☐ with flood-resistant cover for central friction bolt

**Locks:**

☐ Profile cylinder

☐ Panic locks

☐ Panic bar handle "Pushbar"

☐ Overhead door closer

**Manufacturer's proof:**

Torbau Schwaben GmbH

Enzianstraße 14

D-88436 Oberessendorf

Tel.: +49 (0) 7355 -93 100

URL: [www.AquaLOCK.info](http://www.AquaLOCK.info)

Email: [info@AquaLOCK.info](mailto:info@AquaLOCK.info)

Quantity: .....pc      Price: .....€      Total: .....€