

1. TBS AquaLOCK® Quickwall 25**1.1 Type Q25****1.1.1 Flood Protection Floodgate "QUICKWALL" Anodized Aluminium**

Quickwall 25 floodgate. Tested according to EVH quality and test regulations VR-No. 20890 Flood-resistant according to IFT guideline FE-07/1-2005

Brand: AquaLOCK Quickwall

Single-wing floodgate. Used for heavy rain or firefighting water retention. Stop type DIN right or DIN left. Special hinge function for rapid insertion into the opening to be protected. Material: Aluminium, Silver EV1 anodized, age-resistant seal made of high-pressure-resistant EPDM, quadruple seal. Leakage 0.0 liters/m/min. Suspension device for proper, seal-friendly storage. Building connection profiles: Aluminium Silver EV1 anodized

Installation dimension (W x H mm) : _____ x _____

Quantity: _____

Supply and install according to manufacturer's instructions.

Size range:

Width: 450 - 2500 mm

Height: 410 - 2300 mm

Stop type:

☐ DIN right

☐ DIN left

Design:

☐ With building connection profiles

☐ With anodized aluminium floor plate for levelling unevenness

Special equipment:

☐ Slide bolt in the middle downwards

Manufacturer's proof:

Torbau Schwaben GmbH

Enzianstraße 14

D-88436 Oberessendorf

Tel.: +49 (0) 7355 – 93 100

URL: <http://www.AquaLOCK.info>

Email: info@aqualock.info

Quantity:pc Price:€ Total:€