

TESTING COMPLETED IN ACCORDANCE WITH ANSI/DASMA 105-2020

Submitted to:

Torbau Schwaben GmbH Enzianstraße 14, 88436 Eberhardzell Deutschland

Report No.: AT-00858

Product Type: Garage Door

Product Series/Model: AquaLock Garage Door
Overall Test Specimen Dimensions: 3048mm (W) x 3048mm (H)

(120in x 120in)

Test Specimen Thermal Transmittance (U): 2.91 W/(m² °K), (0.51 BTU/(hr ft² °F))

Air Infiltration Rate @ 75 Pa (1.57 psf): 6.01 L/s-m² (1.20 CFM/ft²)

Report Date: 2021/12/21

Revision Date N/A **Number of Pages:** 6

Note: Reference must be made to UL Laboratory Canada Inc.. complete report for test specimen description and detailed test results.

Prepared by:

Frédéric Currier

Thermal Evaluation Department UL Laboratory Canada Inc.

Approved by:

Marilyne Thibault B. Sc.

Person In Responsible Charge UL Laboratory Canada Inc.

LABORATORY, FIELD TESTING AND ADVISORY SERVICES FOR THE BUILDING ENVELOPE

TORONTO

7 Underwriters Road
Toronto
ON M1R 3A9
Canada
T: +1.866.937.3852
E: BuildingEnvelope@ul.com

MONTREAL

1320 Lionel-Boulet Blvd Varennes QC J3X 1P7 Canada T: +1.855.353.2532 E: BuildingEnvelope@ul.com TELFORD Halesfield 2

Telford
TF7 4QH
United Kingdom
T: +44.1952.586.580
E: BuildingEnvelopeEurope@ul.com

W: ul.com/buildingenvelope